

MINI HD265

Full HD Digital HEVC Satellite Receiver with Over-The Top Content with card reader



H.265
HEVC

FAST SCAN
EASY INSTALLATION

	MULTIMEDIA PLAYBACK*								weather forecast		RSS READER	
<small>audio and video codecs are subjects to availability*</small>												

MAIN FEATURES

- One Conax embedded smart card reader
- HEVC decoding support
- 6000 channels (TV and Radio) programmable
- Two High Speed USB 2.0 Connections
- Ethernet Connection & USB WiFi Support (Ralink RT5370 chip only)
- RSS Reader & Weather Forecast Function
- Channel Recording to External Storage Devices (optional)
- Timeshift support
- Channel Recording & Timeshifting Simultaneously (optional)
- Channel switching time less than 1 second
- True-color, User Friendly On-Screen Display (OSD)
- Full Picture In Graphic (PIG) function
- Electronic Program Guide (EPG)
- Subtitle supported
- Parental lock facility by channel and program event
- Program and Channel information transfer from receiver to receiver
- Satellite Blind Scan & Fast Scan support
- DiSEqC 1.0, 1.1, 1.2 and USALS Compatible
- Full HD (1080p) Output via Digital Video Output
- Exciting games embedded
- Multi-Language support
- Software upgrade support via USB, Network, OTA, RS232
- Power Consumption in Stand-By: <0.5W

*Features and specifications are subject to change without notice

MINI HD265



TECHNICAL SPECIFICATIONS

Tuner & Demodulation

Tuner Type:

Input Connector:

Signal Level:

LNB Power & Polarization:

Current:

22KHz Tone Frequency:

DiSEqC Control:

Demodulation:

Input Symbol Rate:

FEC:

DVB-S / DVB-S2

F-type, Connector, Female

-65 to -25 dBm

Vertical: +13V/+14V,

Horizontal: +18V/+19V

Max. 400mA (Overload Protection)

22±1KHz

Version 1.0, 1.1, 1.2, USALS

QPSK, 8PSK

2-45 Mbps,

1/2, 2/3, 3/4, 5/6, 7/8 and Auto

MPEG TS A/V Decoding

Transport Stream:

Input Rate:

Aspect Ratio:

Video Decoding:

Video Resolution:

Audio Decoding:

Audio Mode:

Sampling Rate:

MPEG-2, H.264, H.265

Max.120Mbit/s

4:3, 16:9, Letter Box

MPEG-4/H.265 SP@L3 to ASP@L5, AVC,

HP@level 4.1, MP@level 4.1

720*480P/I, 720*576P/I, 1280*720p,

1920*1080i, 1920*1080p

MPEG-1/2,AAC-LC,HE-AAC,MP3,Dolby Digital

Left / Right / Stereo/ Mono

32, 44.1 and 48KHz

System Resources

Main Processor:

Flash Memory:

DDR3 RAM:

800MHz CPU

16MB

256MB

Power Supply

Input Voltage:

12V DC

Power Consumption:

24W Max

Stand-By Power Consumption:

<0.5W

A/V & Data Input/Output

RCA:

RS-232C:

USB:

S/PDIF:

Digital Video Output:

Ethernet:

IR IN:

CVBS Video out, L&R Audio out

Jack-type, Transfer rate 115.2Kbps, 9 pin D-sub

Type

Two USB 2.0 slots

Coaxial

VER1.4, Type A

10/100M RJ45

Jack-type, External IR sensor connection

Physical Specifications

Size[W*H*D]:

144mm x 40mm x 110mm

Net Weight:

0.5KG

Operation Temperature:

0°C~+45°C

Storage Temperature:

-10°C~+70°C

Storage Humidity:

5%~95% RH (Non-Condensing)