AMIKO MultiTracker 3

User's Manual

www.amikostb.com

1. INTERFACE, BUTTONS AND INDICATORS
1.1 INTERFACE:
1.2 BUTTONS AND INDICATORS2
2. BASIC FUNCTIONS
2.1 Satellite4
2.1.1 Satellite > TP Control4
2.1.2 Satellite >Measure5
2.1.3 Spectrum Analyzer6
2.1.4 Satellite > Constellation7
2.1.5 Satellite > Edit Satellite8
2.1.6 Satellite > Dish Set-up10
2.1.7 Satellite > Angle Calculation13
2.2Terrestrial14
2.2.1Terrestrial > Scope15
2.2.2 Terrestrial>Measure16
2.2.3Terrestrial > Spectrum17
2.2.5 Terrestrial>Channel Edit19
2.2.6Terrestrial > Edit Emetteur19
2.3 Cable
2.3.1Cable > TILT21
2.3.2 Cable>Measure21
2.3.3 Cable>Spectrum22
2.3.4 Cable>Constellation22
2.3.5 Cable>Channel Edit22
2.4 DV IN
2.5 USB
2.6 System24
2.7. Play Program Menu25
2.8 Screenshot27
2.9 Debug information27
3. Safety Instructions

1. INTERFACE, BUTTONS AND INDICATORS

1.1 INTERFACE:



DC 12V IN: The DC power supply in jack of meter. Please check the output voltage of adapter carefully before plug-in. The meter would be damaged if the input voltage is higher than 12V.

USB: The USB port for USB device to plug-in.

DV IN: The digital video input port.

RESET: The reset button of the meter.

AV OUT: The analog video and audio output port.

RF IN: The antenna or LNB RF signal input port. RF type, female.

1.2 BUTTONS AND INDICATORS



0-1

SCREEN: The screen for display for meter

Indicators:

POWER: The red LED will be on if the meter is working

RF POWER: The yellow LED will be on if the power supply of LNB/antenna is on

LOCK: The green LED will be on if the connected signal locks

CHARGE: The LED will be RED if the meter is in-charging. And it will be green if the battery if full

Buttons:

POWER: Press and hold on about 3 second to turn on or turn off the meter

MENU: Enter or exit menu

EXIT: Exit current menu or current operation

0~9 NUMBER KEYS: Input numeric values. Please refer to help bar of each menu for other functions

 $\blacktriangle/ \mathbf{\nabla}$: Zapping channels or navigation in the menu

 \checkmark Decrease or increase the volume or navigation in the menu

OK: Enter channel list menu in video playing screen; in other menu, press to confirm your selection

or operation

2. BASIC FUNCTIONS

Turn on the power switch and then the device will enter to Main Menu. Press [EXIT] to enter video playing menu. Press OK to enter submenu to analyzer or set parameters. Press [$\checkmark / \checkmark / \checkmark / \checkmark$] to navigation.



Items	Instructions
Satellite	Functions for satellite. Press [OK]/ • to enter right function items. Press [EXIT]/ • to exit
	back to left.
Terrestrial	Functions for terrestrial. Press [OK]/ > to enter right function items. Press [EXIT]/ < to
	exit back to left.
Cable	Functions for cable. Press [OK]/ > to enter right function items. Press [EXIT]/ < to exit
	back to left.
DV In	DV input function. Press [OK] to enable digital video input by DV IN port. Press [EXIT] to
	back.
USB	Functions about USB sticker. Upgrade software, import/export satellite and TV channels.
System	The meter system settings

2.1 Satellite



The functions for satellite digital signal. Press [▲/▼] to navigation. Press [OK] to enter sub-menu.

Items	Instructions
TP Control	Show 4 transponders signal status on one screen.
Measure	Show many testing results of input signal. Such as strength, quality, CNR, BER
Spectrum	Show the spectrum chart of input satellite signal
Constellati	Show the constellation chart of input satellite signal
on	
Edit	Edit the saved satellites parameters, such as edit, add and delete
Satellite	
Dish Set-up	Set dish parameters for satellites. Such as LNB type, DiSEqC, motor type
Angle	Calculate the antenna elevation and azimuth according to the local position. And also the
Calculation	meter can simulate aligning progress of antenna.

2.1.1 Satellite > TP Control

The menu show 4 transponders testing results on one screen. And also show the satellite orbital position from real signal if it is available in the in transponder stream. The face icon set to smile one if the real orbit in the transponder stream is same to the current selected satellite in the meter.

Press to pop-up transponders list to change the current transponder



2.1.2 Satellite >Measure

The menu shows many testing results of input signal. Press [\checkmark/\checkmark] to switch items and press [\checkmark/\checkmark] to change curser focus between satellite and transponder.

Satellite > I	Measure		13V 22K				
SATIAS	TRA 2, 28,2	:≣ \$ T	♦ TP: 11910/V/27500				
CBER	<1.0E-07	60	C/N	24.5 dB			
LBER	<1.0E-09	ΟΟ dBμV	LKM	16.6 dB			
Feed Voltage	0.0 V		Feed Current	0 mA			
ONID	0x013e	DVB-S2	TSID	0x24b8			
		8-PSK-3/4	Orbital Position	013.0° E			
S: 88 %							
		Q: 99 %					

MENU Ut	ility
Items	Instructions
13V	The LNB power supply status of LNB. The values are 13V, 18V and off
22K	The 22K status of LNB. The values are 22K and off
SAT:	Show and choose the satellite. Press [\checkmark / \checkmark] to change, or press [OK] to enter satellite list
TP:	Show and choose the transponder. Press $[\blacktriangle/ \lor]$ to change, or press [OK] to enter
	transponder list. Press numeric button to enter edit pop-up window.
CBER	The testing result of CBER
C/N	The C/N ratio of signal
LBER	The testing result of LBER
LKM	The testing result of LKM
Feed	The feed voltage of LNB
Voltage	

Feed	The feed current of LNB
Current	
ONID	The original network identification from transponder stream
TSID	The transponder stream identification from transponder stream
60 dBµV	The power level of input signal of current transponder
Face Icon	It sets to green smile one if the signal is locked, or set to red sad one
DVB-S2	The satellite system of input signal
8-PSK 3/4	The demodulation mode and FEC value of input signal
Orbit	The satellite orbit value from transponder stream
Position	
S:	The signal strength in percent
Q:	The signal quality in percent

Press [MENU] to pop-up window to search channels on single transponder or all transponders mode and to enter to zoom function. Press [OK] to enter channel search menu. The meter will enter to channel play menu if the search progress is finished.

 Satellite > Measure
 18V
 22K
 §

 SAT: THOR 0.8
 TP: 11910/H/27500
 57

 CNR
 23.2 dB
 57

 CBER
 <1.0E-07</td>
 dBuv

 LBER
 <1.0E-09</td>
 OPSK 9/10

 Orbital Position
 013.0° E
 EXIT Exit

Switch curser to Zoom and press OK button to enter zoom menu. The screenshot of zoom function as below:

2.1.3 Spectrum Analyzer

The menu display the spectrum chart of input signal.

Satellite	> Spectru	m		1	3V 22K	6
100		97 180				
80		l l l				
60						
40 20-		-		allamant	um a di	
0						
0 950.0	1150.0	1350.0	1550.0	1750.0	1950.0	2150.0
0 950.0 Centre	1150.0 e Freq	1350.0	1550.0	1750.0 Frequency	1950.0 /	2150.0
0 950.0 Centre 1 Span 2	1150.0 е Freq 00 мнz 2	1350.0 1350 Mi Span 400	1550.0	1750.0 Frequency Span 800 MH	1950.0 z 4 Sp	2150.0 FFI Mmr an 1200 MHz

	Instructions
Button 1	Press [1] to set the frequency range to 200MHz around current set frequency
Button 2	Press [2] to set the frequency range to 400MHz around current set frequency
Button 3	Press [3] to set the frequency range to 800MHz around current set frequency
Button 4	Press [4] to set the frequency range to 1200MHz around current set frequency
Button 5	Press [5] to switch between Analyze and Pause status
Button 7	Press [7] to switch between LO Low and LO High if the LNB type is double values
Button 8	Switch LNB voltage output between 13V and 18V

Press [OK] to check the current frequency is be locked or not on blind mode. The real frequency, symbol rate and also the satellite orbit if the value is available in the transponder stream.

2.1.4 Satellite > Constellation

The menu shows the constellation chart of input signal if the current transponder is locked. And also the C/N ratio, power level, CBER, DVB system and demodulation mode.

Press $[\land / \checkmark / \land / \land]$ to change current transponder. Press [OK] to pop-up transponders list to help to select easily.



2.1.5 Satellite > Edit Satellite

The menu can edit, add and delete satellites and also transponders of satellite. Press [\langle / \rangle] to focus satellites list or transponders list of selected satellite.

Edit Sa	tellite			6		
001 A	STRA 1,	19,2	10727 /H	i/ 30000		
002 H	OTBIRD;	13.	10758 /\	// 27500		
003 A	STRA 2,	28,2	10775 /H	/ 29900		
004 A	STRA 3,	23,5	10796 /\	// 27500		
005 A	STRA 4,	4,8	10815 /H/ 27500			
006 AMOS 2,3, 4 10834 /V/ 27500						
Edit Sa	atellite	2 Add Satellite	3 Delete Satellite	(4) Save		
			Instructions			
[OK]/[1]	Press to sho	w edit dialog to edit satel	lite name, orbit and positi	on		
[2]	Press this button to add new satellite					
	Step1: Set the satellite name, longitude and location					
	Step2: Set the antenna parameters for the satellite					
[3]	Press this b	outton to delete current s	elected satellite. A dialog	will display on screen, user		
	can confirm	or cancel the delete oper	ation			
[4]	Press this b	utton to save all the modi	fications			

Edit satellites (when satellite item is selected)

Edit Satellite	
001 ASTRA 1, 19,2	10727 /H/ 30000
002 HOTBIRD, 13	10758 /V/ 27500
Edit Sa	tellite
Name	HOTBIRD, 13
Longitude	13.0
Location	East
ОК	Cancel

Edit Satellite



Delete satellite confirm dialog

Edit S	Satellite									6
001	ASTRA 1, 19,2	8		î		107	27 /F	4/ 30	000	8
002				44						
	Extend	A	в	с	D	E	F	G	н	
	Caps Off	t	J	к	L	м	N	0	Р	
	Back	Q	R	s	т	U	v	w	×	
Lor	ок	Y	z	0	1	2	3	4	5	
LOC	Cancel	6	7	8	9	1	?	#		
	ОК					C	ance	I		

Edit satellite name dialog

Edit transponder (when transponder list is selected)

User can edit, add and delete transponder in this menu.

Edit Satellite			
001 ASTRA 1,	19,2	10727 /	/ 30000
002 HOTBIRD,	13	10758 /V	/ 27500
003 ASTRA 2,	28,2	10775 /H	/ 29900
004 ASTRA 3,	23,5	10796 /\	/ 27500
005 ASTRA 4,	4,8	10815 /H	/ 27500
006 AMOS 2,3	, 4	10834 /v	/ 27500
	2	3	4
Edit TP	Add TP	Delete TP	Save

2.1.6 Satellite > Dish Set-up

All the parameters of dish will be set on this menu. Such as LNB type, LNB power, motor type...

Satellite > Dish Set-up	
Satellite	🔹 ASTRA 3, 23,5 🕨
LNB type	Universal
LO.LOW	9750
Lo.High	10600
22KHz	AUTO
LNB power	AUTO
Switch Type	DISEQC1.0
Switch Input	1
Centre Freq	0000
Motor	Fixed
OK Satellite List	MENU Auto DiSEqC

Press [▲ / 🗸 / 🗸 /	/▶]	to navigation.
---------------------	-----	----------------

	Instructions				
Satellite	Show and choose satellites. Press [\checkmark / \blacktriangleright] to select satellite, or press [OK] to enter Satellite				
	list.				
LNB Type	Set LNB Type, press [◀ / ▶] button to switch between values. Default set to UNIVERSAL				
LO.LOW	Show the low local oscillator value. Use digital button to input the LO.LOW once the LNB Type				
	is customized				
LO.HIGH	Show the low local oscillator value. Use digital button to input the LO.HIGH once the LNB Type				
	is customized				

22KHz	Set 22K status. Press [4 / >] button to switch between ON/OFF/Auto. Default set to Auto			
LNB	Set the antenna power. Press [\checkmark / \blacktriangleright] button to switch between Auto/13V/18V/OFF. Default			
Power	set to Auto			
Switch	Set DiSEqC type. Press [(/)] button to switch between None/DiSEqC1.0/			
Туре	DiSEqC1.1/SCR_PORT_A/SCR_PORT_B/SCD2_PORT_A/SCD2_PORT_B/SCD2_PORT_C/SCD2_P			
	ORT_D. Default set to None			
Switch	Set DiSEqC1.0 or DiSEqC1.1's input port. Or set user band for SCR and SCD2. Default set to			
Input	None			
Centre	Set user band frequency for SCR and SCD2			
Freq				
Motor	Set antenna motor type. Press [\checkmark / \blacktriangleright] button to switch between Fixed / DiSEqC1.2/USALS.			
	Default set to Fixed			

Press [MENU] button to enter auto DiSEqC function dialog. The meter will find out the connected port of DiSEqC 1.0 automatically. The switch type will set to DiSEqC 1.0 if the connected port is found.



DiSEqC 1.2:

On this menu, user can set the antenna to right position by DiSEqC 1.2 command if the antenna supported DiSEqC 1.2 function.

According to the signal strength and quality in percent, the meter can get the best signal by sending command to adjust antenna to right position.

Positioner Set-up	13V 22K
Satellite	HOTBIRD, 13
Transponder	< 11881/V/27500 >
Move	<-Stop->
Centre position	ок
Set limit	Disable
Save	ОК
	S: 93 %
	Q: 99 %

	Instructions
Satellite	Show the current selected satellite.
Transponde	Show and choose the current transponder of the satellite. Press [\checkmark / \blacktriangleright] to switch between
r	transponders.

Move	Press [4 / >] to send command to move antenna to East or West by step mode. Press [4 / >]
	and hold on to send command to move antenna to East or West by continual mode. Press
	[EXIT] to send pause command to exit moving progress.
Centre	Press [OK] to send command to move antenna to centre position
position	
Set limit	Press [4 / >] button to send command to set limitation to move to East or West
Save	Press [OK] to send saving command to save current antenna position for satellite

USALS:

On this menu, user can set the antenna to right position by USALS command if the antenna supported USALS function.

User can select the local city in the saved cities list. The local longitude and latitude will be set as saved in the meter once the city sets. Or user can press [OK] to edit the local longitude and latitude manually if the city sets to customized.

Press [1] to send command to move antenna to the right position.

Press [2] to send command to move antenna to centre position.



GOTO X SE	T-UP		6
N.	HOT	BIRD, 13	
	\bigcirc	\$7.74	
	\oplus	West	
	\bigcirc	25.1°	
	\oplus	South	
	99	%	
Move to position	on Move To Centre		

Edit local longitude and latitude

2.1.7 Satellite > Angle Calculation

The menu calculates the right azimuth and elevation of antenna according to the satellite orbit and testing local longitude and latitude.



	Instructions				
HOTBIRD,13	The current selected satellite. Press [4 / >] to switch satellites. Press [OK] to enter the				
	satellite list to select				
Ankara	The default cities list. The local longitude and latitude will be set once the city is selected.				
	Or user can press [OK] to edit the local longitude and latitude manually if the city sets to				
	customized.				
39.4	The elevation of antenna to align to the current satellite				
209.4	The azimuth of antenna to align to the current satellite				
-22.1	The polarization of antenna				

Press [2] to enter compass menu. The menu try to simulate the align progress of antenna to find out the best elevation and azimuth by moving the direction and angle of meter.



Press [3] to enter align menu. The menu try to lead user to find out the right elevation and azimuth of antenna by moving the direction and angle of meter.



2.2Terrestrial

This menu for DVB-T/T2 functions. Please see below screenshot

Ŕ	Satellite	Sco	ope 📋
(((²)))	Torroctrial	🙆 Mea	isure
A	Terrestrial	۲۹ Spec	trum
P	Cable	Conste	ellation
	DV In	Chann	el Edit
	USB	Edit Er	netteur
	000		
Ø	System		

Press [\checkmark / \checkmark] to navigation and press [OK] to enter into sub-menus.

	Instructions
Scope	The menu shows four channels` signal testing results on one screen
Measure	The menu shows many testing results for selected channel
Spectrum	The menu shows spectrum chart of input signal
Constellation	The menu shows constellation chart of selected channel once it is locked
Channel Edit	User can edit channel's parameter on this menu, such as frequency, system type and
	bandwidth
Edit	Select correct channels that can available of testing field on this menu.
Emetteur	

2.2.1Terrestrial > Scope

The menu shows four channels' signal testing results on one screen. The meter will check channels one by one automatically.



Press [OK] to pop-up channels list to help to select channel to replace the current focused one. Press [MENU] to pop-up emittor list to help to switch emittors easily.

2.2.2 Terrestrial>Measure

Terrestrial > Measure							
Emetteur5 CH		23 490.00 MHz		DVB-T 8 MHz			
CBER			6	5	M	IER	
LBER				82 авич		Pattern	PP6
Feed Voltage	0.0 V 0 mA 0×2114 0×0202		DVB-T2 16-QAM 5/6		Cell ID FFT Mode Guard Interval		4444
Feed Current							32 K
ONID							1/32
TSID					NIT Version		4
S: 00 %							
	Q: 00 %						

The menu shows many testing results for selected channel. Please see below screenshot for detail.

MENU Utility

	Instructions			
Emetteur5	The testing field name. Press $[\checkmark/\checkmark]$ to switch values and press [OK] to pop-up list to			
	help to select easily.			
CH:	The channel name Press $[\checkmark/\checkmark]$ to switch values and press [OK] to pop-up list to help			
	to select easily.			
490.00 MHz	The frequency of channel			
DVB-T 8 MHz	The terrestrial system and bandwidth. Press $[\checkmark/\checkmark]$ to switch values and press [OK] to			
	pop-up list to help to select easily.			
CBER	The CBER value of input signal			
MER	The MER value of input signal			
LBER/VBER	The LBER/VBER value of input signal.			
Pilot Pattern	The pilot pattern value of input signal			
Feed Voltage	The feed voltage value of antenna			
Feed Current	The feed current value of antenna			
Cell ID	The cell ID value of input signal			
FFT Mode	The FFT mode of input signal			
ONID	The original network identification of input transport stream			
TSID	The transport stream identification			
Guard Interval	The guard interval value of input signal			
NIT Version	The version value of network identification table			
82 dBuV	The power level of input signal			
DVB-T2	The digital system of terrestrial of input signal			
16-QAM 5/6	The modulation and FEC value of input signal			

S:	The strength of signal in percent
Q:	The quality of signal in percent

Press [MENU] to pop-up window to help to search channels or set power supply to antenna.

Terrestrial >	Terrestrial > Measure						
Emetteu	r5	CH: 23	490.00 M	Hz	DVB-T	2 8 MHz	
CBER	<1.0E-	07	51	1	MER	36.7 dB	
LBER	<1.0E-	09 🤇		Pilot	Pattern	PP6	
Search programs on actual channel							
Search programs on all channels							
		Anttenna	a power 5V	1			
Anttenna power 12V							
Anttenna power 18V							
		Anttenna	power 24	V			

2.2.3Terrestrial > Spectrum

The menu shows spectrum chart of input signal



	Instructions
Centre	The current frequency to show power level value
Freq	
118	The power level value of current frequency
dBuV	
Channel	The name of channel which frequency is close to current frequecny.
No.	

Button 1	Press [1] to set the frequency range to 200MHz around current set frequency
Button 2	Press [2] to set the frequency range to 400MHz around current set frequency
Button 3	Press [3] to set the frequency range to 600MHz around current set frequency
Button 4	Press [4] to set the frequency range to 800MHz around current set frequency
Button 5	Press [5] to switch between Analyze and Pause status
▲/▼	To set the power level range of spectrum chart
	To set the current frequency

2.2.4 Terrestrial > Constellation

Please refer to 2.1.4.

2.2.5 Terrestrial>Channel Edit

User can edit channel parameters on this menu. All the channels for terrestrial will be listed on this menu. Press $[\checkmark/\checkmark]$ to switch channels.

Terre	estrial > Chan	nel Edit			
ID	Channel No.	Frequency	Туре	Band Width	
1	5	177.50 MH2	Ť	7 MHz	
2	6	184.50 MHz	т	7 MHz	
3	7	191.50 MHz	т	7 MHz	
4	8	198.50 MHz	т	7 MHz	
5	9	205.50 MHz	т	7 MHz	
6	10	212.50 MHz	Т	7 MHz	
7	11	219.50 MHz	Т	7 MHz	
OK E	nter Edit Mode	ME	NU Exit		

Press [OK] to enter the edit mode. And then press [4 / >] to switch between frequency, type and bandwidth

Terrestrial > Channel Edit					
ID	Channel No.	Frequency	Туре	Band Width	
1	8	177.50	T	7 MHz	
2	6	184.50 MHz	Τ	7 MHz	
3	7	191.50 MHz	т	7 MHz	
4	8	198.50 MHz	Т	7 MHz	
5	9	205.50 MHz	т	7 MHz	
6	10	212.50 MHz	т	7 MHz	
7	11	219.50 MHz	Т	7 MHz	
OK E	inter Edit Mode	MEX	Exit		

2.2.6Terrestrial > Edit Emetteur

Choose the available channels for each Emetteur on this menu. Press $[\bigstar/\checkmark]$ or $[\bigstar/\checkmark]$ to navigation and press [MENU] to edit the name of current emetteur.

All the channels list on the right screen. The channels with red rectangle belong to current selected emetteur. Press

[OK] to add or delete from the emetteur.

errestrial > Edit E	metteu	ir							
Bordeaux bouliac									
Cahors 2	5	6	7	8	9	10	11	12	21
Lyon Pilat	22	23	24	25	26	27	28	29	30
Metz	31	32	33	34	35	36	37	38	39
Nantes Paris	40	41	42	43	44	45	46	47	48
Emetteurl	49	50	51	52	53	54	55	56	57
Emetteur2 Emetteur3	58	59	60	61	62	63	64	65	66
Emetteur4	67	68	69						
Emetteur5	L:4								

2.3 Cable

This menu for digital cable functions.

R	Satellite		(TILT)	
((²)))	Terrestrial		Measure	
8	Terrestinai	<u>ا</u> م	Spectrum	
P	Cable		Constellation	
	DV In		Channel Edit	
	USB			
ø	System			

Items	Instructions
TILT	The menu shows four channels signal testing results on one screen
Measure	The menu shows many testing results of channels
Spectrum	The menu shows spectrum chart for cable signal
Constellation	The menu shows constellation chart for digital cable signal
Channel Edit	User can edit channel parameters on this menu. Such as frequency, digital cable system
	and symbol rate

2.3.1Cable > TILT

The menu shows four channels` signal testing results on one screen. The meter will check channels one by one automatically.



Press [OK] to pop-up channels list to help to select channel to replace the current focused one.

2.3.2 Cable>Measure

The menu shows testing results for digital cable signal. And also can search programs once the signal is locked.

Cable > M	easure			
CH: EOS	i≣ 🗢 🛛 FRE	E: 177.50 MHz	SYM:	6875
CBER	<1.0E-07	73 _{dBµv}	ONID	0x013e
PER	<1.0E-06		TSID	0x24b8
MER	38.2 dB	64-QAM		
		S: 95 %		
		Q: 99 %		
MENU Utility				

	Instructions
CH:	The channel name Press $[\checkmark/\checkmark]$ to switch values and press [OK] to pop-up list to help
	to select easily.
FRE:	The frequency of channel
SYM:	The symbol rate of channel
CBER	The CBER value of input signal

PER	The PER value of input signal
MER	The MER value of input signal
ONID	The original network identification of input transport stream
TSID	The transport stream identification
73 dBuV	The power level of input signal
DVB-C	The digital system of cable of input signal
64-QAM	The modulation value of input signal
S:	The strength of signal in percent
Q:	The quality of signal in percent

2.3.3 Cable>Spectrum

Please refer to 2.2.3

2.3.4 Cable>Constellation

Please refer to 2.1.4

2.3.5 Cable>Channel Edit

User can edit channel parameters on this menu. All the channels for terrestrial will be listed on this menu. Press [/] to switch channels.

Cable > Channel Table					
ID	Channel No.	Frequency	Туре	Symb.rate	
1	£05	177.50 MHz	(C	6875	1
2	E06	184.50 MHz	с	6875	
3	E07	191.50 MHz	С	6875	
4	E08	198.50 MHz	С	6875	
5	E09	205.50 MHz	С	6875	
6	E10	212.50 MHz	С	6875	
7	E11	219.50 MHz	с	6875	
OK Enter Edit Mode		ME	∾ Exit		

Press [OK] to enter the edit mode. And then press [4 / >] to switch between frequency, type and bandwidth

2.4 DV IN

Press [OK] to switch to digital video input mode. The screen will display content which transports by digital video cable. All the functions for DVB signal are unavailable right now. Press [EXIT] to exit DV in mode and back to testing mode.



2.5 USB

This sub-menu include functions about USB sticker. User can upgrade software, import/export satellites parameters and import/export TV/Radio channels by USB sticker.



How to update software by USB sticker:

- 1. Copy the official release .AP file software to USB sticker
- 2. Plug-in USB sticker to the meter
- 3. Move the curse to USB item on Main Menu

4. Press [OK] to pop-up .AP file lists. Switch cursor to the correct file item, then press [OK] to confirm to update.

5. The meter will enter into updating mode and reboot automatically once the updating progress is finish.

Note: Please do not power off the meter during the whole updating progress.

How to export satellites to USB sticker:

1. Plug-in USB sticker to meter

2. Switch cursor to Export satellite to USB

3. The meter will export all the saved satellite parameters to USB stick and save the file as Multi_Tracker_3 (xx-xx-xx xx).SAT.

How to import satellite from USB sticker:

1. Copy the exported satellite file from other meter to USB sticker or export satellite to USB sticker from other meter

2. Plug-in USB sticker to the meter which needs to import satellites

3. Switch cursor to Import Satellite By USB item

4. Press OK button to pop-up the match file(.SAT) list. Switch cursor to the right file item and then press OK buttont to comfirm and start imporing progress

5. Press EXIT to exit once the success information displays on the screen.

How to export channel to USB sticker:

- 1. Plug-in USB sticker to meter
- 2. Switch cursor to Export channel to USB

3. The meter will export all the saved digital channels to USB stick and save the file as Multi_Tracker_3 (xx-xx-xx xx-xx).CHL.

How to import channel from USB sticker:

1. Copy the exported channel file from other meter to USB sticker or export channel to USB sticker from other meter

- 2. Plug-in USB sticker to the meter which needs to import satellites
- 3. Switch cursor to Import Channel By USB item
- 4. Press OK button to pop-up the match file list. Switch cursor to the right file item and then press
- OK buttont to comfirm and start imporing progress
- 5. Press EXIT to exit once the success information displays on the screen.

2.6 System

The system setting menu for meter.

R	Satellite		G
		Language Select	English
۳Å	Terrestrial	Factory Reset	ок
0		Time Zone	GMT +1
₿	Cable	Lock Alarm	Off
	DV In	Key Tone	On
		Auto Power Off	Off
	USB	Time	26/06/2007 19:00
ö	System	Software Version	3.1

	Instructions	
Language select	Set the OSD language. Press [◀ / ▶] to switch between available languages. Default set to	
	English	
Factory reset	Press [OK] to pump factory reset confirm dialog. Press [OK] again to do reset or [Exit] to	
	cancel. The meter will reset all the setting values to default if do a factory reset.	
Time Zone	Set the local time zone. Press [
Lock alarm	Press [◀ / ▶] to set the lock alarm On or Off. Default set to On	
Key tone	Press [4 / >] to set the key tone On or Off. Default set to On	
Auto power off	The finder will power off according to your setting. Press [$4 / 1$] to switch options.	
	Default set to Off	
Time	Press [OK] to set the current time manually	
Software	Show the software version	
Version		

2.7. Play Program Menu

All the searched and saved programs can play on this menu. User also can enjoy the digital video and audio. Press [EXIT] to exit information bar. Press [\checkmark / \checkmark] to adjust volume and press [\checkmark / \checkmark] to zap programs.

0014 Planeta Sport DV352 0	
	8:21
S: 95 % Q: 99 %	
Service ID H/M Video PID HI Provider M Audio PID HI PID Audio 1: M PID Audio 2: M PCR PID HI PMT PID HIM TS Bitrate HIM Transponder HIMM Filler Filler Filler	

Press [OK] to pop-up program list to show all saved programs.

TV List	DV3S
0001 Planeta Sport	
0002 KTO	
0003 BET	
0004 BBC World	
0005 C1R-Europe	
0006 CNNi	8
0007 Euronews	6
0008 JSTV1	8
THOR 0.8 11910 H 2750	0
OK Confirm 🚯 Edit 🔤	🔍 Find
2 Switch to DVB-T/T2	Radio

On program channels menu, press [\checkmark / \checkmark] to switch programs and press [OK] to confirm to play the selected program.

Press [1] to switch between TV list and radio list.

Press [MENU] to pop-up keyboard to find out channels by setting letters.

Press [2] to switch program list between DVB-S/S2, DVB-T/T2 and DVB-C.

Press [3] to enter edit program menu:

Program Edit	
	E at
0001 Planeta Sport	
0002 KTO	Freq.
0003 BET	11910
0004 BBC World	Sym.
0004 BBC World	27500
0005 C1R-Europe	
0006 CNNi	
Move 🛛 Lock 🚯 Delet	e 🐠 Edit Name

Press [1] to start move the focused program, press [\checkmark/\checkmark] to change the position in the list and then press [OK] to confirm to move the program to the current position.

Press [2] to lock/unlock the current focused program.

Press [3] to delete the current focused program.

Press [4] to edit the name of current focused program.

2.8 Screenshot

The meter support screenshot function and save the BMP picture to USB sticker.

How to get a screenshot:

- 1. Plug-in USB sticker to the meter
- 2. Press [MENU] and [OK] button at the same time
- 3. The meter will show the name of screenshot on the screen
- 4. Wait a while to save file to USB sticker before plug-out
- 5. All the screenshot will be saved in the root of USB sticker

2.9 Debug information

The meter support export some debug information to USB sticker. The debug information will be saved as txt file.

How to get debug information

- 1. Plug-in USB sticker to the meter
- 2. Enter into Main Menu
- 3. Press [MENU] to pop-up a confirm dialog
- 4. Select YES to enter debug mode
- 5. Then, do your testing operation as usual
- 6. Enter into Main Menu and press [MENU] to exit debug mode and save debug information to USB sticker
- 7. Wait a while for saving data before plug-out USB sticker

NOTE: User need to enter into Main Menu and press [MENU] to exit debug mode manually, or the debug information can't save into USB sticker.

3. Safety Instructions

•Never spill liquids of any kind on the equipment. Liquids increase the risk of electric shock and damage to the equipment.

•The equipment is not shockproof. Do not use the unit as a hammer and take care that it cannot fall from a great height.

•Do not immerse the equipment in water. Avoid moisture and store the equipment in a dry place.

•Observe the specifed power supply. Only use the mains adapter supplied to charge the unit.

CAUTION:

•The battery used can present danger of fire or chemical burn if it is severely mistreat. Do not disassembly, cremate or heat the battery above 60°C under no circumstances.

•The battery is losing storage capacity as you go through its life. Contact your distributor when necessary to replace the battery.

To extend battery life the user should follow these tips:

•In case of providing a long inactivity period of the equipment it is advisable to make every 3 months a charge / discharge cycle and a subsequent partial charge (40% aprox.).

•It is advisable to keep it in a cool place and away from heat.

•You should avoid keeping the battery for a long period of time at full load or fully discharged.

•There is not necessary to wait to fully discharge before a charge because these batteries have no memory effect.